

APPLICATION



If contaminated, use a claybar to clean the paint and wheels. If paint correction is required do so before application.



Wash and completely dry surfaces to be coated.



Clean the paint using a 50% IPA (isopropyl alcohol) to water mix in a trigger sprayer. Mist the paint then wipe down with a microfiber towel.



Wipe on coating by hand using a sponge or coating block, panel by panel. After wiping on wait 30-90 seconds to flash (depending on temp) then buff off with a microfiber towel.



Wait 20 minutes before driving, and 4 hours before getting wet.

PRO

CERAMIC NANO COATING

PRODUCT OVERVIEW



System X Pro is a super slick super hydrophobic ceramic coating for automotive paint. Pro is a semi-permanent 9H self cleaning ceramic coating with high gloss.

Pro has passed rigorous Boeing approval testing and has been evaluated for hardness as well as alkali and salt resistance by SGS laboratory. This ensures Pro is 100% safe for your paint, adheres on a molecular level, and withstands tough environmental conditions.

Pro has a **SIX YEAR WARRANTY** on most cars when installed by an Accredited Installation Center and annual inspection requirements are met.

TECHNICAL DATA

EFFECTIVENESS	6+ years depending on environmental factors
PENCIL HARDNESS	9H (7H scratch hardness)
APPLICATION	By hand with sponge, coating block or cotton applicator
BOTTLE SIZE	65 mL
SHELF TIME	1 years from shipment date when unopened and stored dry at 18°C (64°F) to 23°C (73°F)
APPEARANCE	Clear / High Gloss
FILM THICKNESS	.75 - 1 µm
CHEM. RESISTANCE	Excellent
TEMP. RESISTANCE	> 760°C (1400°F)
SALT SPRAY	(ASTM B117) @ 35°C (95°F), 5% salt concentration, > 350 hrs to first signs of corrosion
ADHESION CROSS-CUT TAPE	(ASTM D3359) 5b (0%, none)
MANDREL BEND	(ASTM D522) 0% @ 180° rotation
IMPACT	(ASTM D2794) 80/80 in/lbs
COVERAGE	60 sqft / ounce (30 ml)
DRY TIME	20 minutes
CURE TIME	Initial cure in 4 hours, full cure in 3 days

